

Boat Manufactured By:



1392 Remmel Dam Rd. • Malvern, AR 72104

(501) 566-1525

www.verandamarine.com

VERANDA V ONE

Length	25' 0"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	4,200 lbs
Maximum HP	425 hp
Fuel Capacity	55 gal
Weight as Tested	6,033 lbs

XF425XSB

Horsepower	425 hp
Induction	DI/VCT/DOHC
Displacement	5.6L
Weight (Estimated)	952 lbs
Gear Ratio	1.79:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#4
------------------------	----

PROPELLER(S)

Series	XTO OS
Diameter x Pitch	16-5/8 x 19
Yamaha Part #	6GR-45974-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	65° F / 57° F
Elevation (in feet above sea level)	299.7'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 2 people, 55 gallons of fuel, 2 batteries, safety, and test equipment.

YPB#: PB_VER_V ONE__XF425XSB_04/08/22_PNT



Engine: Yamaha XF425XSB

Boat: Veranda V ONE

Configuration: Single

Test Date: 8-Apr-2022



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.0	1.9	2.61
1500	7.8	2.8	2.84
2000	9.8	4.1	2.39
2500	17.2	5.9	2.94
3000	22.5	8.2	2.76
3500	27.8	11.2	2.49
4000	32.9	14.7	2.23
4500	38.2	19.4	1.97
5000	43.6	25.3	1.73
5500	47.8	34.0	1.41
5900	52.3	35.9	1.46
0-20 MPH: 4.03 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.