

Boat Manufactured By:

Everglades™ by Dougherty

544 Airpark Road • Edgewater, FL 32132

(386) 409-2202

www.evergladesboats.com

EVERGLADES® 255 CC

Length	24' 7"
Beam	9' 3"
Dry Weight (Boat Mfr. Pub)	5,800 lbs
Maximum HP	500 hp
Fuel Capacity	154 gal
Weight as Tested	8,080 lbs

F250XCA / LF250XCA

Horsepower	250 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	562 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series 11™
Diameter x Pitch	15 1/4 x 19
Yamaha Part #	6CE-45970-00-00 / 6CF-45970-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	82° F / 80° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 1/2 tank of fuel, 3 batteries, safety and test gear.

YPB#: PB_EVG_255CC_t_F250XCA_2016-05-25_OCC

Engine: Yamaha F250XCA /

F250XCA / LF250XCA

LF250XCA

Boat: Everglades® 255 CC

Configuration: Twin

Test Date: 25-May-2016

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6.1	2.5	2.44
1500	8.3	4.4	1.89
2000	9.1	7.3	1.25
2500	13.4	10.7	1.25
3000	22.3	13.3	1.68
3500	32.5	16.3	1.99
4000	38.3	21.6	1.77
4500	44	28	1.57
5000	48.4	32.4	1.49
5500	53.3	44.7	1.19
5800	57.2	50	1.14
0-30 MPH: 5.84
			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.