

Boat Manufactured By:

JUPITER

1103 12th Avenue East • Palmetto, FL 34221

(941) 729-5000

www.jupitermarine.com

JUPITER 40

Length	39' 11"
Beam	11' 11"
Dry Weight (Boat Mfr. Pub)	16,000 lbs
Maximum HP	1,350 hp
Fuel Capacity	500 gal
Weight as Tested	21,306 lbs

LXF450XSA2 / XF450ESA2 / XF450XSA2

Horsepower	450 hp
Induction	DI/VCT/DOHC
Displacement	5.6L
Weight (Estimated)	963 - 1,010 - 963 lbs
Gear Ratio	1.79:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
------------------------	----

PROPELLER(S)

Series	XTO Offshore
Diameter x Pitch	16-1/8 x 22
Yamaha Part #	6GS-45934-20-00 / 6GR-45976-20-00 / 6GR-45934-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	3
Air / Water Temperature (Fahrenheit)	80° F / 78° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 275 gallons of fuel, 5 batteries, safety and test gear.

YPB#: PB_JUP_40_TR_LXF450XSA2_2-8-2024_OCC



Engine: Yamaha LXF450XSA2 / XF450ESA2 / XF450XSA2

Boat: Jupiter 40

Configuration: Triple

Test Date: 8-Feb-2024



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6.2	5.4	1.14
1500	8.8	9.5	0.93
2000	10.2	15.8	0.65
2500	13.9	23.7	0.59
3000	21.1	31.9	0.66
3500	30.0	37.9	0.79
4000	38.2	51.5	0.74
4500	44.9	64.2	0.70
5000	50.5	81.6	0.62
5500	56.4	104.3	0.54
5950	60.8	114.7	0.53
0-20 MPH: 6.86 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.