PERFORMANCE BULLETIN

Boat Manufactured By:

SEA PRO

25214 Hwy 121 • Whitmire, SC 29178
(803) 694-2644
seapromfg.com

SEA PRO 240 DUAL CONSOLE

Length	23' 9"
Beam	8' 10"
Dry Weight (Boat Mfr. Pub)	4,300 lbs
Maximum HP	350 hp
Fuel Capacity	102 gal
Weight as Tested	5,556 lbs

F300XCB2

Horsepower	300 hp
Induction	EFI
Displacement	4.2L
Weight (Estimated)	556 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	3/4" Above Bottom

PROPELLER(S)

TEST CONDITIONS

Number of People	1
Air / Water Temperature (Fahrenheit)	88° F / 85° F
Elevation (in feet above sea level)	150'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 60 gallons of fuel, 2 batteries, safety and test equipment.

YPB#: PB_SEP_240_Dual_Console_F300XCB2_9-6-2024_ODC



Engine: *Yamaha F300XCB2*

Boat: *Sea Pro 240 Dual Console*

Configuration: *Single*

Test Date: *6-Sep-2024*



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.5	1.4	3.93
1500	8.1	2.3	3.52
2000	10.5	3.7	2.84
2500	13.2	5.2	2.54
3000	17.0	6.1	2.79
3500	**27.4**	**8.1**	**3.38**
4000	33.1	10.7	3.09
4500	38.0	14.1	2.70
5000	42.7	17.5	2.44
5500	47.0	23.2	2.03
5900	**50.2**	**26.7**	**1.88**

**Time to Plane: 4.25 seconds
 0-30 MPH: 6.25 seconds**

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.