

Boat Manufactured By:

SEA FOX

BOAT WORKS
 2550 Highway 52 • Moncks Corner, SC
 (843) 761-6090
www.seafoxboats.com

SEA FOX 328 COMMANDER

Length	32' 0"
Beam	10' 8"
Dry Weight (Boat Mfr. Pub)	8,975 lbs
Maximum HP	900 hp
Fuel Capacity	311 gal
Weight as Tested	12,383 lbs

F300USB2 / LF300USB2

Horsepower	300 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	624 - 624 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	3/4" Above Boat Bottom

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15-1/4 x 18
Yamaha Part #	6CE-45934-20-00 / 6CF-45934-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	89° F / 83° F
Elevation (in feet above sea level)	0'
Wind Velocity	15-20 MPH

COMMENTS

Test weight includes 250 gallons of fuel, 4 batteries, safety and test equipment.

YPB#: PB_SFX_328 Commander_TW_F300USB2_8-6-2023_OCC



Engine: Yamaha F300USB2 / LF300USB2

Boat: Sea Fox 328 Commander

Configuration: Twin

Test Date: 6-Aug-2023



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	7.2	2.7	2.67
1500	9.0	4.3	2.10
2000	10.7	7.1	1.51
2500	12.6	10.5	1.20
3000	16.0	13.3	1.20
3500	28.6	18.1	1.58
4000	33.7	23.6	1.43
4500	39.9	31.1	1.28
5000	44.2	39.5	1.12
5500	49.2	52.0	0.95
5800	52.0	52.6	0.99

Time to Plane: 5.85 seconds / **0-30 MPH: 7.74 seconds**

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.