PERFORMANCE BULLETIN

Boat Manufactured By:

One Skeeter Road • Kilgore, TX
(903) 984-0541
www.skeeterboats.com



SKEETER SX241

Length	24' 1"
Beam	8' 5"
Dry Weight (Boat Mfr. Pub)	2,925 lbs
Maximum HP	350 hp
Fuel Capacity	75 gal
Weight as Tested	4,714 lbs

F350XSA2

Horsepower	350 hp
Induction	EFI/VCT/DOHC
Displacement	4.3L
Weight (Estimated)	629 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15 x 21
Yamaha Part #	6CE-45972-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	80° F / 84° F
Elevation (in feet above sea level)	374'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 40 gallons of fuel, 4 batteries, 2 people, 36 volt trolling motor, T-top, 12" Hydralic jackplate, safety and test equipment.

YPB#: PB_SKT_SX241_F350XSA2_08-04-24_BAY

Engine: *Yamaha F350XSA2*

Boat: *Skeeter SX241*

Configuration: *Single*

Test Date: *4-Aug-2024*



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.6	1.2	4.52
1500	7.1	2.1	3.40
2000	9.3	3.6	2.55
2500	14.9	5.3	2.79
3000	**27.7**	**7.1**	**3.92**
3500	34.4	9.0	3.84
4000	39.2	12.6	3.11
4500	43.8	15.9	2.75
5000	48.9	20.7	2.36
5500	54.4	26.5	2.06
6100	**60.0**	**30.6**	**1.96**

0-20 MPH: 5.60 seconds

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.