PERFORMANCE BULLETIN

Boat Manufactured By:

JEANNEAU
105 Eastern Avenue #202 • Annapolis, MD 21403
(410) 280-9400
www.jeanneau.com

JEANNEAU® NC 895

Length	29' 9"
Beam	9' 9"
Dry Weight (Boat Mfr. Pub)	6,746 lbs
Maximum HP	400 hp
Fuel Capacity	159 gal
Weight as Tested	8,964 lbs

F200XCA / LF200XCA

Horsepower	200 hp
Induction	EFI
Displacement	2.8 L
Weight (Estimated)	489 lbs
Gear Ratio	1.86

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2

PROPELLER(S)

Series	Reliance® Series
Diameter x Pitch	14 1/2 x 15
Yamaha Part #	68F-45970-10-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	27° F / 42° F
Elevation (in feet above sea level)	211'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 50 gallons of fuel, 3 batteries, generator, Premiere Package, Comfort Package, safety and test gear.

YPB#: PB_JEA_NC895_t_F200XCA_2016-09-18_OWA

Engine: *Yamaha F200XCA / LF200XCA*

Boat: *Jeanneau® NC 895*

Configuration: *Twin*

Test Date: *18-Sep-2016*

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.8	1.6	3
1500	6.3	2.6	2.42
2000	7.8	4.2	1.86
2500	9.2	6.5	1.42
3000	10.2	9.6	1.06
3500	17.1	12.7	1.35
4000	**26.8**	**14.8**	**1.81**
4500	32	18.9	1.69
5000	36.5	25.5	1.43
5500	40.2	32.5	1.24
5950	**44**	**39.5**	**1.11**

**0-20 MPH: 7.18
**

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.