

Boat Manufactured By:

Albemarle
THE CAROLINA CLASSIC
 140 Midway Drive • Edenton, NC 27932
 (252) 482-7600
 www.albemarleboats.com

ALBEMARLE 27DC

Length	27' 4"
Beam	8' 8"
Dry Weight (Boat Mfr. Pub)	8,000 lbs
Maximum HP	500 hp
Fuel Capacity	170 gal
Weight as Tested	10,406 lbs

F250UCA / LF250UCA

Horsepower	250 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	575 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15-1/4 x 19
Yamaha Part #	6CE-45970-20-00 / 6CF-45970-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	49° F / 48° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 130 gallons of fuel, 3 batteries, safety and test equipment.

YPB#: PB_ALB_27DC_TW_F250UCA_11-19-19_OCC



Engine: Yamaha F250UCA / LF250UCA

Boat: Albemarle 27DC

Configuration: Twin

Test Date: 19-Nov-2019



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6.5	2.6	2.55
1500	8.4	4.4	1.91
2000	9.9	7.4	1.34
2500	13.5	11.2	1.21
3000	19.4	13.5	1.44
3500	32.0	16.6	1.93
4000	37.5	21.9	1.71
4500	42.7	28.3	1.51
5000	47.6	36.6	1.30
5500	52.2	45.0	1.16
5900	57.7	50.4	1.14
0-30 MPH: 5.80 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.