

Boat Manufactured By:



BENNINGTON
 2805 Decio Drive • Elkhart, IN 46514
 (0:(574) 264-6336)
 www.benningtonmarine.com

BENNINGTON 198 SL

Length	19' 10"
Beam	8' 0"
Dry Weight (Boat Mfr. Pub)	2,108 lbs
Maximum HP	115 hp
Fuel Capacity	24 gal
Pontoons Diameter	CMS.Helpers.HTMLHelper.StripTags(Html.Raw(Model.BoatPontoonDiameter).ToString())
Weight as Tested	3,088 lbs

F115LB

Horsepower	115 hp
Induction	EFI/DOHC
Displacement	1.8L
Weight (Estimated)	377 lbs
Gear Ratio	2.15:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#1
------------------------	----

PROPELLER(S)

Series	Talon GP™
Diameter x Pitch	13-5/8
Yamaha Part #	6FP-45941-00-00
Propeller Material	Aluminum

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	62° F / 70° F
Elevation (in feet above sea level)	850"
Elevation (in feet above sea level)	5-10 MPH

COMMENTS

Test weight includes 15 gallons of fuel, 1 battery, safety and test equipment.

YPB#: PB_BNT_198_SL_F115LB_8-17-20_PNT



Engine: Yamaha F115LB

Boat: Bennington 198 SL

Configuration: Single

Test Date: 13-Aug-2020



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	3.4	0.5	6.80
1500	5.1	0.9	5.94
2000	6.3	1.2	5.21
2500	7.7	1.9	4.05
3000	11.3	2.5	4.50
3500	15.1	3.2	4.79
4000	19.0	3.9	4.94
4500	23.4	4.8	4.86
5000	27.0	5.9	4.62
5500	30.2	7.6	4.00
6300	35.2	10.7	3.29
0-20 MPH: 6.12 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.